



## STANDARD

Base in AISI 304 stainless steel | Display area in AISI 304 stainless steel | Exterior decoration in skinplate | AISI 304 stainless steel worktop | Polyurethane injected sides | Multiplexible | Ventilated refrigeration | Digital thermometer | Electronic temperature controller | Programmable automatic defrosting | Electric evaporation of defrost water | Tempered glasses | Adjustable stainless steel feet

## OPTIONS

Quartz worktop | Display area in painted plate (RAL) | Exterior decoration in painted plate (RAL) | Exterior decoration in AISI 304 stainless steel | Treated evaporator | Reversible fan motors | Additional socket | Joining kit | Castors with brakes | Adjustable stainless steel high feet | Voltage 115 V-60 Hz / 120 V-60 Hz / 220 V-60 Hz



Ventilated



0/4 °C




Automatic



LED



230V | 1 Ph | 50 Hz



M2 | 25 °C | 60% R.H.



Plug-in



R290 ECO Friendly

C100 SS	100	130	150	200	250	300
Operating temperature	0/4 °C	0/4 °C	0/4 °C	0/4 °C	0/4 °C	0/4 °C
Refrigerant (ref/GWP)	R290/3	R290/3	R290/3	R290/3	R290/3	R290/3
Defrost	Time	Time	Time	Time	Time	Time
External dimensions (LxDxH) (mm)	1025x1100x881	1325x1100x881	1525x1100x881	1970x1100x881	2570x1100x881	2970x1100x881
TDA - Total display area (m <sup>2</sup> )	1,07	1,35	1,53	1,96	2,52	2,89
Net volume (l)	172	226	262	343	452	525
Refrigerated shelf area (m <sup>2</sup> )	0,77	1,01	1,17	1,53	2,02	2,34
Insulation	PUR/H2O	PUR/H2O	PUR/H2O	PUR/H2O	PUR/H2O	PUR/H2O
Nominal power (W)	1107	1073	1085	1398	1455	1474
Electric current (A)	5	5,2	5,3	6,8	7,2	7,2
TEC - Total energy consumption (kWh/24h)	5,452	5,961	6,150	6,621	7,452	7,973
AEC - Annual energy consumption (kWh/annum)	1989,98	2175,77	2244,75	2416,30	2719,98	2910,15
Energy efficiency class*						

\* The information presented regarding the energy class (Energy Labeling regulation and Eco Design regulation) is only related to the standard models. For the energy class of the equipments with different options that involve elements of energy consumption and/or changes in the construction of the unit, please contact the manufacturer directly.  
 \*\* Pictures and colors are not contractual. The information presented refers to the standard equipments in plug-in version. For additional information about remote our neutral units, contact the manufacturer.

