



### STANDARD

4 levels of removable, adjustable, and tiltable shelves | Self-closing hinged front doors with double tempered glass | Display area in skinplate | Exterior decoration in skinplate | Solid sides | Ventilated refrigeration | Vertical LED lighting | Electronic temperature controller | Programmable automatic defrosting | Automatic evaporation of defrost water | Adjustable feet

### OPTIONS

Display area in painted plate (RAL) | Exterior decoration in painted plate (RAL) | Treated evaporator | Castors with brakes | Voltage 115 V-60 Hz / 120 V-60 Hz / 220 V-60 Hz



Ventilated



-21/-18 °C | 0/4 °C



Automatic



LED



230V | 1 Ph | 50 Hz



L1/M1 | 25 °C | 60% H.R.



Plug-in







R290 ECO Friendly

EIGER

130

190

Operating temperature	-21/-18 °C   0/4 °C	-21/-18 °C   0/4 °C
Refrigerant (ref/GWP)	R290/3	R290/3
Defrost	Electric	Electric
External dimensions (LxDxH) (mm)	1300x788x2034	2000x788x2034
TDA - Total display area (m <sup>2</sup> )	1,32	2,13
Net volume (l)	530	867
Refrigerated shelf area (m <sup>2</sup> )	2,30	3,77
Insulation	PUR/H2O	PUR/H2O
Nominal power (W)	1408	2906
Electric current (A)	7,24	14,23
TEC - Total energy consumption (kWh/24h)	21,350   9,18	28,700   12,33
AEC - Annual energy consumption (kWh/annum)	7794,21   3351,43	10475,50   4498,63
Energy efficiency class*	   	   

\* The information presented regarding the energy class (Energy Labeling regulation and Eco Design regulation) is only related to the standard models. For the energy class of the equipments with different options that involve elements of energy consumption and/or changes in the construction of the unit, please contact the manufacturer directly.  
 \*\* Pictures and colors are not contractual. The information presented refers to the standard equipments in plug-in version. For additional information about remote our neutral units, contact the manufacturer.

