



## STANDARD

4 levels of removable, adjustable, and tiltable shelves | Self-closing hinged front doors with double tempered glass | Rear doors | Display area in skinplate Exterior decoration in skinplate | Display sides with double tempered glass | Multiplexible | Ventilated refrigeration | Vertical LED lighting | Electronic temperature controller | Programmable automatic defrosting | Adjustable feet

## OPTIONS

Upper sling bar for hooks | Display area in painted plate (RAL) | Display area in AISI 304 stainless steel | Exterior decoration in painted plate (RAL) | Exterior decoration in AISI 304 stainless steel | Treated evaporator | LED lighting on shelves | Solid sides | Panoramic sides | Supplementary shelves level without lighting | Supplementary shelves level with lighting | Joining kit | Voltage 115 V-60 Hz / 120 V-60 Hz / 220 V-60 Hz



Ventilated



0/4 °C



Automatic



LED



230V | 1 Ph | 50 Hz



M1 | 25 °C | 60% H.R.



Plug-in



R290 ECO Friendly

F080 DA	130	190	250	310	370
Operating temperature	0/4 °C	0/4 °C	0/4 °C	0/4 °C	0/4 °C
Refrigerant (ref/GWP)	R290/3	R290/3	R290/3	R290/3	R290/3
Defrost	Time	Time	Time	Time	Time
External dimensions (LxDxH) (mm)	1307x883x2230	1912x883x2230	2522x883x2230	3127x883x2230	3732x883x2230
TDA - Total display area (m²)	2,42	3,35	3,92	4,76	5,60
Net volume (l)	735	1102	1471	1837	2204
Refrigerated shelf area (m²)	2,98	4,48	5,99	7,48	8,97
Insulation	PUR/H2O	PUR/H2O	PUR/H2O	PUR/H2O	PUR/H2O
Nominal power (W)	775	912	1550	1687	1824
Electric current (A)	4,14	4,78	8,28	8,92	9,56
TEC - Total energy consumption (kWh/24h)	8,973	12,841	17,946	21,814	25,682
AEC - Annual energy consumption (kWh/annum)	3275,15	4686,97	6550,29	7962,11	9373,93
Energy efficiency class*					

\* The information presented regarding the energy class (Energy Labeling regulation and Eco Design regulation) is only related to the standard models. For the energy class of the equipments with different options that involve elements of energy consumption and/or changes in the construction of the unit, please contact the manufacturer directly.

\*\* Pictures and colors are not contractual. The information presented refers to the standard equipments in plug-in version. For additional information about remote our neutral units, contact the manufacturer.

