



## STANDARD

4 levels of removable, adjustable, and tiltable shelves | Display area in skinplate | Exterior decoration in skinplate | Display sides with double tempered glass | Multiplexible | Ventilated refrigeration | LED top lighting | Electronic temperature controller | Programmable automatic defrosting | Adjustable feet | Night curtain  
(Only available in remote version )

## OPTIONS

Upper sling bar for hooks | Display area in painted plate (RAL) | Display area in AISI 304 stainless steel | Exterior decoration in painted plate (RAL) | Exterior decoration in AISI 304 stainless steel | Treated evaporator | LED lighting on shelves | Solid sides | Panoramic sides | Supplementary shelves level without lighting | Supplementary shelves level with lighting | Joining kit | Voltage 115 V-60 Hz / 120 V-60 Hz / 220 V-60 Hz



Ventilated



0/4 °C



Automatic



LED



230V | 1 Ph | 50 Hz



M1 | 25 °C | 60% H.R.



Plug-in



R290 ECO Friendly

F080 SS	130	190	250	310	370
Operating temperature	0/4 °C	0/4 °C	0/4 °C	0/4 °C	0/4 °C
Refrigerant (ref/GWP)	R290/3	R290/3	R290/3	R290/3	R290/3
Defrost	Time	Time	Time	Time	Time
External dimensions (LxDxH) (mm)	1307x800x1973	1912x800x1973	2522x800x1973	3127x800x1973	3732x800x1973
TDA - Total display area (m <sup>2</sup> )	2,14	3,12	4,11	5,09	6,07
Net volume (l)	613	919	1226	1530	2204
Refrigerated shelf area (m <sup>2</sup> )	2,34	3,50	4,68	5,85	8,97
Insulation	PUR/H2O	PUR/H2O	PUR/H2O	PUR/H2O	PUR/H2O
Nominal power (W)	66	101	132	167	202
Electric current (A)	0,53	0,79	1,06	1,32	1,58

\* Pictures and colors are not contractual. The information presented refers to the standard equipments in plug-in version. For additional information about remote our neutral units, contact the manufacturer.

