



STANDARD

4 levels of removable and adjustable shelves | Self-closing pivoting front doors with double tempered glass | Interior in skinplate | Exterior in skinplate | Ventilated refrigeration | Vertical LED lighting | Two-way fan motors | Electronic temperature controller | Programmable automatic defrosting | Automatic evaporation of defrost water | Castors

OPTIONS

Voltage 115 V-60 Hz / 120 V-60 Hz / 220 V-60 Hz



Ventilated



0/4 °C



Automatic



LED



230V | 1 Ph | 50 Hz




M1 | 25 °C | 60% R.H.



Plug-in



R290 ECO Friendly

Operating temperature	0/4 °C
Refrigerant (ref/GWP)	R290/3
Defrost	Time
External dimensions (LxDxH) (mm)	588x593x1795
TDA - Total display area (m ²)	0,49
Net volume (l)	149
Refrigerated shelf area (m ²)	0,87
Insulation	PUR/H2O
Nominal power (W)	441
Electric current (A)	2,48
TEC - Total energy consumption (kWh/24h)	3,537
AEC - Annual energy consumption (kWh/annum)	1291,01
Energy efficiency class*	

* The information presented regarding the energy class (Energy Labeling regulation and Eco Design regulation) is only related to the standard models. For the energy class of the equipments with different options that involve elements of energy consumption and/or changes in the construction of the unit, please contact the manufacturer directly.
 ** Pictures and colors are not contractual. The information presented refers to the standard equipments in plug-in version. For additional information about remote our neutral units, contact the manufacturer.

