



STANDARD

3 levels of removable, adjustable, and tiltable shelves | Display area in skinplate | Exterior decoration in lacquered MDF (RAL) | Sliding rear doors | Multiplexible | Ventilated refrigeration | Top LED lighting | Shelves LED lighting | Digital thermometer | Front glass anti-condensation system | Electronic temperature controller | Programmable automatic defrosting | Electric evaporation of defrost water | Tilting front glass | Tempered glasses | Double-glass sides | Adjustable feet

OPTIONS

Display area in painted plate (RAL) | Display area in AISI 304 stainless steel | Treated evaporator | Additional socket | Joining kit | Castors with brakes | Adjustable stainless steel high feet | Voltage 115 V-60 Hz / 120 V-60 Hz / 220 V-60 Hz



Ventilated



2/5 °C



Automatic



LED



230V | 1 Ph | 50 Hz



M2 | 25 °C | 60% H.R.



Plug-in



R290 ECO Friendly

P072 VD	100	130	150	200
Operating temperature	2/5 °C	2/5 °C	2/5 °C	2/5 °C
Refrigerant (ref/GWP)	R290/3	R290/3	R290/3	R290/3
Defrost	Time	Time	Time	Time
External dimensions (LxDxH) (mm)	995x710x1371	1295x710x1371	1495x710x1371	1940x710x1371
TDA - Total display area (m ²)	1,83	2,35	2,70	3,48
Net volume (l)	167	221	257	334
Refrigerated shelf area (m ²)	1,23	1,63	1,89	2,46
Insulation	PUR/H2O	PUR/H2O	PUR/H2O	PUR/H2O
Nominal power (W)	1121	1187	1464	1614
Electric current (A)	5,25	5,93	7,29	8,02
TEC - Total energy consumption (kWh/24h)	9,922	11,930	13,240	18,614
AEC - Annual energy consumption (kWh/annum)	3621,53	4354,45	4832,6	6794,11
Energy efficiency class*				

* The information presented regarding the energy class (Energy Labeling regulation and Eco Design regulation) is only related to the standard models. For the energy class of the equipments with different options that involve elements of energy consumption and/or changes in the construction of the unit, please contact the manufacturer directly.
 ** Pictures and colors are not contractual. The information presented refers to the standard equipments in plug-in version. For additional information about remote our neutral units, contact the manufacturer.

