



STANDARD

Display area in skinplate | Exterior decoration in skinplate | Ventilated refrigeration | LED lighting | Electronic temperature controller | Programmable automatic defrosting | Electric evaporation of defrost water | Castors

OPTIONS

1 level of foldable shelf | Trolley for transport | Voltage 115 V-60 Hz / 120 V-60 Hz / 220 V-60 Hz



Ventilated



0/4 °C



Automatic



LED



230V | 1 Ph | 50 Hz



M1 | 25 °C | 60% H.R.




Plug-in



R290 ECO Friendly

UNO**50**

Operating temperature (°C)	0/4 °C
Refrigerant (ref/GWP)	R290/3
Defrost	Time
External dimensions (LxDxH) (mm)	474x465x1026
TDA - Total display area (m ²)	0,48
Net volume (l)	49
Refrigerated shelf area (m ²)	0,13
Insulation	PUR/H2O
Nominal power (W)	662
Electric current (A)	3,44
TEC - Total energy consumption (kWh/24h)	4,375
AEC - Annual energy consumption (kWh/annum)	1596,88
Energy efficiency class*	

* The information presented regarding the energy class (Energy Labeling regulation and Eco Design regulation) is only related to the standard models. For the energy class of the equipments with different options that involve elements of energy consumption and/or changes in the construction of the unit, please contact the manufacturer directly

** Pictures and colors are not contractual. The information presented refers to the standard equipments in plug-in version. For additional information about remote our neutral units, contact the manufacturer.

