



## STANDARD

Display area in skinplate | Exterior decoration in skinplate | Ventilated refrigeration | LED lighting | Digital thermometer | Electronic temperature controller | Programmable automatic defrosting | Automatic evaporation of defrost water | Castors with brakes | Bumper

## OPTIONS

Voltage 115 V-60 Hz / 120 V-60 Hz / 220 V-60 Hz



Ventilated



0/4 °C



Automatic



LED



230V | 1 Ph | 50 Hz



M2 | 25 °C | 60% R.H.




Plug-in



R290 ECO Friendly

**V100 PT****150**

Operating temperature (°C)	0/4 °C
Refrigerant (ref/GWP)	R290/3
Defrost	Temperature
External dimensions (LxDxH) (mm)	1566x1060x997
TDA - Total display area (m <sup>2</sup> )	1,75
Net volume (l)	294
Refrigerated shelf area (m <sup>2</sup> )	1,18
Insulation	PUR/H2O
Nominal power (W)	522
Electric current (A)	2,96
TEC - Total energy consumption (kWh/24h)	3,461
AEC - Annual energy consumption (kWh/annum)	1263,27
Energy efficiency class*	

\* The information presented regarding the energy class (Energy Labeling regulation and Eco Design regulation) is only related to the standard models. For the energy class of the equipments with different options that involve elements of energy consumption and/or changes in the construction of the unit, please contact the manufacturer directly.  
\*\* Pictures and colors are not contractual. The information presented refers to the standard equipments in plug-in version. For additional information about remote our neutral units, contact the manufacturer.

