



## STANDARD

4 levels of removable, adjustable, and tiltable shelves | Display area in skinplate | Exterior decoration in skinplate | Display sides with double tempered glass | Multiplexible | Ventilated refrigeration | LED top lighting | Electronic temperature controller | Programmable automatic defrosting | Electric evaporation of defrost water | Adjustable feet | Night curtain

## OPTIONS

Upper sling bar for hooks | Display area in painted plate (RAL) | Display area in AISI 304 stainless steel | Exterior decoration in painted plate (RAL) | Exterior decoration in AISI 304 stainless steel | Treated evaporator | LED lighting on shelves | Solid sides | Panoramic sides | Supplementary shelves level without lighting | Supplementary shelves level with lighting | Joining kit | Castors with brakes | Voltage 115 V-60 Hz / 120 V-60 Hz / 220 V-60 Hz



Ventilated



2/5 °C



Automatic



LED



230V | 1 Ph | 50 Hz



M2 | 25 °C | 60% R.H.



Plug-in



R290 ECO Friendly

W080 SS	70	100	130	150	200	250	300
Operating temperature	2/5 °C	2/5 °C	2/5 °C	2/5 °C	2/5 °C	2/5 °C	2/5 °C
Refrigerant (ref/GWP)	R290/3	R290/3	R290/3	R290/3	R290/3	R290/3	R290/3
Defrost	Time	Time	Time	Time	Time	Time	Time
External dimensions (LxDxH) (mm)	737x800x1952	1037x800x1952	1272x800x1952	1537x800x1952	1982x800x1952	2452x800x1952	2983x800x1952
TDA - Total display area (m <sup>2</sup> )	0,98	1,38	1,68	2,03	2,61	3,25	3,95
Net volume (l)	265	389	485	595	777	971	1189
Refrigerated shelf area (m <sup>2</sup> )	1,32	1,94	2,42	2,96	3,78	4,85	6,52
Insulation	PUR/H2O	PUR/H2O	PUR/H2O	PUR/H2O	PUR/H2O	PUR/H2O	PUR/H2O
Nominal power (W)	1413	1611	1636	2556	2975	3272	5112
Electric current (A)	7,3	7,9	8,1	13,3	14,7	16,3	26,6
TEC - Total energy consumption (kWh/24h)	12,838	15,103	17,360	19,699	22,653	33,703	39,304
AEC - Annual energy consumption (kWh/annum)	4685,87	5512,60	6336,40	7190,14	8265,35	12301,60	14345,96
Energy efficiency class*							

\* The information presented regarding the energy class (Energy Labeling regulation and Eco Design regulation) is only related to the standard models. For the energy class of the equipments with different options that involve elements of energy consumption and/or changes in the construction of the unit, please contact the manufacturer directly.

\*\* Pictures and colors are not contractual. The information presented refers to the standard equipments in plug-in version. For additional information about remote our neutral units, contact the manufacturer.

